

GRIVEN

KOLORSTREAM

2500W DMX Outdoor Colour Wash

For buildings up to 150m high



*** * * * Weatherproof * * * ***

Architectural Colour Changer

- For walls, buildings, monuments etc. to a height of 150 m
 - Variable radiation angle (12° - 22°)
- Colour-changer with cyan, magenta, yellow for infinite colour-variations
 - With strobe-, dimmer- and blackout-function
- Control unit for adjusting the DMX-starting address, switching the lamp, reading out the operating hours of the lamp
 - DMX-512 controlled
- Stand-alone operation possible via pre-programmed sequences
 - Master/Slave-operation possible
- For extremely bright 2500 W HMI G-38 lamp

The success, on a worldwide scale, of outdoor colour changer units and the growing interest from the developing architectural lighting sector persuaded us to develop and create a new projector for long throw applications. KOLORSTREAM was the result, and uses an HMI 2500W lamp (G38 base) and a nickel rhodium plated high reflectivity optical system with a variable angle (12° to 33° high brightness beam, with the ability to highlight buildings up to 150m high. CYM subtractive colour mixing gives many spectacular colour hues, and the detachable ballast unit, separable by up to 20m, makes the projector lighter and simpler to install and transport.

Eight factory programmed inbuilt colour sequences can be selected and scene change duration set via on board control, for stand alone operation, and multiple units can be synchronised via the master/slave function. All functions can alternatively be controlled from standard DMX 512.

The aluminium and galvanized steel body is weatherproofed to certified IP44 rating and coated with black epoxy paint.

KOLORSTREAM TECHNICAL SPECIFICATIONS

- LAMP SOURCE **NOT INCLUDED**

Type:HMI
Wattage (W):2500
Base:G38
Lamp life (h):500
Lumens:240.000

- COLOURS

Color (MIX):CYM

- PROJECTION

Angle:12°-33°
Zoom:Motorised
Dimmer:Mechanical
Strobe:2,6 Fps

- OPERATION

DMX channels:6
Stand alone:
Master / Slave:
On Board Control:

- HOUSING

Weather protection:IP44
Cooling:FV

- SIZE (mm)

Height:818
Width:624
Depth:630

- WEIGHT (kg)

Main fixture:41 (72 ballast incl.)
Ballast set:31

- POWER

Input (V):230-240
HZ:50-60
AMP:15

More information about Architectural Lighting on
www.premier-solutions.biz